

DURACUSHION III

FLOATING SYSTEM

DURACUSHION III

FLOATING SYSTEM

SYSTEM FEATURES AND BENEFITS

Floating sports floor systme providing shock absorption, consisting in general of a vapor barrier, PVC pads, softwood nailers, plywood subfloor, maple flooring, sanding, sealers, finishes, game lines and wall base.



1) 3/8" (10 mm) Duracushion PVC resilient pads

(2) Nominal 2" x 3" (38 mm x 64 mm) Softwood Sleeper


3 Plywood Subfloor

WALL BASE DETAIL


3" x 4" (76 mm x 102 mm) Vented Rubber Base
2" (51 mm) Expansion Space
15/32" (12 mm) APA Sheeting
Connor 3/8" (10 mm) PVC Pad
Duracushion Sleeper
25/32" x 2-1/4" (20 mm x 57 mm) Laytite Maple
Vapor Barrier

3-1/8" (79 mm)

THRESHOLD DETAIL (optional accessory)



EQUIPMENT DETAIL (optional accessory)



connorfloor.com 1.800.283.9522

SYSTEM TYPE

Floating System

ANCHORAGE

No concrete attachment

SUBFLOOR CONSTRUCTION

Sleeper Plywood

RESILIENCE

PVC Pads

SLAB DEPRESSION

3/8" (10 mm) pad:

25/32" (20 mm) flooring - 3 1/8" (79 mm)

33/32" (26 mm) flooring - 3 3/8" (86 mm)

5/8" (16 mm) pad:

25/32" (20 mm) flooring - 3 3/8" (86 mm)

 $33/32^{\prime\prime}$ (26 mm) flooring - 3 $5/8^{\prime\prime}$ (92 mm)

TESTING LABORATORY

USSL

United States Sports Surfacing Laboratory

CERTIFIED TESTING

Laboratory test equipment calibrated and certified through the ISSS

GREEN STATUS

Managed forests, certification available